# **IOP**science

Home Search Collections Journals About Contact us My IOPscience

Structural and magnetic characterization of large area, free-standing thin films of magnetic ion intercalated dichalcogenides  $Mn_{0.25}TaS_2$  and  $Fe_{0.25}TaS_2$ 

This content has been downloaded from IOPscience. Please scroll down to see the full text.

2016 J. Phys.: Condens. Matter 28 356002

(http://iopscience.iop.org/0953-8984/28/35/356002)

View the table of contents for this issue, or go to the journal homepage for more

Download details:

IP Address: 211.86.158.36 This content was downloaded on 10/04/2017 at 02:56

Please note that terms and conditions apply.

You may also be interested in:

Ultrafast magnetization and structural dynamics in the intercalated transition metal dichalcogenides Fe0.25TaS2 and Mn0.25TaS2 Q Liu, X D Zhu, L H Wang et al.

Resonant elastic soft x-ray scattering J Fink, E Schierle, E Weschke et al.

X-ray absorption spectroscopy on magnetic nanoscale systems for modern applications Carolin Schmitz-Antoniak

Applications of soft x-ray magnetic dichroism G van der Laan

Magnetic reflectometry of heterostructures S Macke and E Goering

Probing single magnetic nanoparticles by polarization-dependent soft x-ray absorption spectromicroscopy A Fraile Rodríguez, A Kleibert, J Bansmann et al.

Charge density waves in strongly correlated electron systems Chih-Wei Chen, Jesse Choe and E Morosan

Wasp-waisted magnetism in hydrothermally grown MoS2 nanoflakes Levna Chacko, A K Swetha, R Anjana et al.

Magnetism in ultrathin film structures C A F Vaz, J A C Bland and G Lauhoff

## Structural and magnetic characterization of large area, free-standing thin films of magnetic ion intercalated dichalcogenides Mn<sub>0.25</sub>TaS<sub>2</sub> and Fe<sub>0.25</sub>TaS<sub>2</sub>

### Th Danz<sup>1</sup>, Q Liu<sup>2</sup>, X D Zhu<sup>3</sup>, L H Wang<sup>4</sup>, S W Cheong<sup>4,5</sup>, I Radu<sup>6</sup>, C Ropers<sup>1</sup> and R I Tobey<sup>2</sup>

<sup>1</sup> 4th Physical Institute–Solids and Nanostructures, University of Göttingen, 37077 Göttingen, Germany

<sup>2</sup> Zernike Institute for Advanced Materials, University of Groningen, 9747AG Groningen, The Netherlands

<sup>3</sup> High Magnetic Field Laboratory, Chinese Academy of Sciences, Hefei 230031,

People's Republic of China

<sup>4</sup> Laboratory for Pohang Emergent Materials and Max Planck POSTECH Center for Complex Phase

Materials, Pohang University of Science and Technology, Pohang 790-784, Korea

<sup>5</sup> Rutgers Center for Emergent Materials and Department of Physics and Astronomy, Rutgers University, New Brunswick, NJ 08901, USA

<sup>6</sup> Max-Born-Institut für Nichtlineare Optik und Kurzzeitspektroskopie, 12489 Berlin, Germany

E-mail: r.i.tobey@rug.nl

Received 17 April 2016, revised 24 May 2016 Accepted for publication 7 June 2016 Published 6 July 2016



#### Abstract

Free-standing thin films of magnetic ion intercalated transition metal dichalcogenides are produced using ultramicrotoming techniques. Films of thicknesses ranging from 30 nm to 250 nm were achieved and characterized using transmission electron diffraction and x-ray magnetic circular dichroism. Diffraction measurements visualize the long range crystallographic ordering of the intercalated ions, while the dichroism measurements directly assess the orbital contributions to the total magnetic moment. We thus verify the unquenched orbital moment in Fe<sub>0.25</sub>TaS<sub>2</sub> and measure the fully quenched orbital contribution in  $Mn_{0.25}TaS_2$ . Such films can be used in a wide variety of ultrafast x-ray and electron techniques that benefit from transmission geometries, and allow measurements of ultrafast structural, electronic, and magnetization dynamics in space and time.


Keywords: intercalated dichalcogenides, thin films, XMCD, ultramicrotomy

(Some figures may appear in colour only in the online journal)

#### 1. Introduction

Transition metal dichalcogenides (TMDCs) are a broad class of layered materials with a variety of structural and electronic properties. Depending on the specific compound and layer stacking, TMDCs can exhibit metallic (e.g. TaS<sub>2</sub>), semimetallic (e.g. WTe<sub>2</sub>), semiconducting (e.g. MoSe<sub>2</sub>), or insulating (e.g. HfS<sub>2</sub>) behaviour [1, 2]. Recent work has focused on the emergence and dynamics of charge density wave formation (commensurate and incommensurate) concomitant with metal-to-insulator transitions [3, 4]. Yet other work dealt with the properties of monolayers of these materials. Loose interlayer bonding via van der Waals forces allows the fabrication of single monolayers of material which often exhibit electronic phases that are starkly different from bulk properties. Studies on monolayers have brought forth possibilities in optoelectronics and valleytronics [5, 6], and spintronics [7].

The intrinsic properties of the bulk materials can be further expanded by *intercalation* of atoms and small molecules between the layers. In particular, the incorporation of 3d



**Figure 1.** (a) Unit cell of 3*d* ion intercalated TMDC samples. Trilayers of tantalum and sulfur are stacked along the *c*-axis. Magnetic ions fit between the layers in specific locations determined by the concentration *y*. (b) Planar view shows the crystallization of intercalants at y = 0.25. (c) 100 nm sample of Mn<sub>0.25</sub>TaS<sub>2</sub>, and (d) 200 nm sample of Fe<sub>0.25</sub>TaS<sub>2</sub> on a 200 lines per inch copper grid.

transition metals results in the onset of an array of magnetic properties which can be tuned by intercalation concentration, choice of intercalated species, and choice of host lattice [8]. In total, the range of magnetic properties is enormous, providing a platform on which to study magnetism and domain structure as well as their dynamics.

Here we discuss a sample preparation technique that provides free-standing thin films of magnetic ion intercalated TaS<sub>2</sub>. In thin film form, these samples open the possibility for a number of magnetization dynamics studies with new techniques such as ultrafast electron diffraction [9, 10] and microscopy [11], as well as x-ray absorption [12], all of which benefit from transmission geometries where the penetration depth of both pump and probe can be easily matched. Moreover, for x-ray absorption studies, the transmission geometry is the most robust when compared to its total electron yield (TIY) or fluorescence yield (FY) counterparts in that it provides a direct measure of dichroic absorption and is unaffected by electronic saturation effects [13]. The samples were prepared using ultramicrotoming techniques [14], and their structural and magnetic properties were measured using transmission electron diffraction and x-ray circular magnetic dichroism, respectively. Two different materials were studied, Mn<sub>0.25</sub>TaS<sub>2</sub> and Fe<sub>0.25</sub>TaS<sub>2</sub>, which differ in their magnetic properties while sharing the same structure.

#### 2. Material description

TMDCs (chemical formula  $MX_2$  where X is a chalcogen and M a transition metal) consist of stacks of X–M–X sandwich layers which are van der Waals bonded along the *c*-axis [15]. Variations in layer stacking result in a wide range of physical

properties, while particular stacking configurations promote intercalation. For  $TaS_2$ , the metallic 2*H* polytype facilitates intercalation. Upon intercalation, the new chemical formula is A<sub>v</sub>MX<sub>2</sub>, which in the context of TMDCs is understood to maintain the MX<sub>2</sub> structure, while new ions are incorporated between the host layers. The process of 3d ion intercalation occurs during the growth phase, for example using iodine vapor transport. Interestingly, particular intercalant concentrations lead to long-range crystalline order of intercalants between the host layers. This is the case for two situations, that of intercalant density y = 1/4 and y = 1/3, where the intercalants form an ordered  $2 \times 2$  or  $\sqrt{3} \times \sqrt{3}$  superlattice, respectively [8, 16, 17]. When such ordered states occur, the intercalated ion is known to reside in specific sites of the host lattice (the trigonal antiprismatic hollow site between the layers of 2H-TaS<sub>2</sub>), ensuring that the local environment of the magnetic ion is unchanged as one varies the intercalant species or host lattice. A three-dimensional view of the crystallographic structure is shown in figure 1(a) with specific emphasis on the location of the intercalant ion between X-M-X sheets. The crystallization of intercalants is best visualized in a planar view along the *c*-axis, as shown in figure 1(b).

Bulk materials are characterized by Curie temperatures of 80 K for  $Mn_{0.25}TaS_2$  [8] and 155 K [18] for Fe<sub>0.25</sub>TaS<sub>2</sub>. The large intercalant-intercalant distance inhibits direct exchange mechanisms, and an indirect RKKY interaction is understood to play a crucial role [8, 19]. In this case, the exchange interaction between local moments is mediated by the conduction electrons of the host lattice. The isolated ions thus exhibit structural aspects reminiscent of local-moment magnetic systems. At the same time, there are indications of itinerant magnetism in  $Mn_{0.25}TaS_2$  due to a strong hybridisation between the intercalant's 3*d* states with the Ta  $5d_{z^2}$  states which form the conduction band [20]. This class of materials thus bridges the divide between truly local-moment magnetism (as in 4*f* systems) and itinerant ferromagnetism observed in 3*d* transition metals.

The two materials are further distinguished by their magnetic orientation. While  $Mn_{0.25}TaS_2$  is an easy plane ferromagnet with low coercivity [21],  $Fe_{0.25}TaS_2$  exhibits a strong out-of-plane magnetic anisotropy with high coercivity [22]. Additionally, as we will confirm,  $Fe_{0.25}TaS_2$  is known to have a large orbital contribution to the magnetization, while the orbital contribution in  $Mn_{0.25}TaS_2$  is fully quenched.

#### 3. Preparation of free-standing thin films

TMDCs can be readily thinned down to monolayer thickness using the 'scotch tape method' [1], as well as by lithium intercalation [23] or by ultrasonification [24]. However, due to charge transfer from the intercalant to the host and a concomitant change of the interlayer bonding towards a covalent bond [25], standard cleaving methods must be abandoned in the case of 3*d* ion intercalated TMDCs. To our knowledge, there have been no reports of exfoliation of thin samples of  $Mn_{0.25}TaS_2$  and  $Fe_{0.25}TaS_2$ . Recently, the preparation of free-standing films of 1T-TaS<sub>2</sub> using an ultramicrotome was reported [26]. The resulting films had lateral dimensions of ~ 200  $\mu$ m and thickness of 30 nm. On the basis of supporting transmission electron microscope (TEM) diffraction images, it has been shown that the crystallinity of the sample and the transition temperatures between the different charge density wave phases are unaffected, and that the preparation principle is suitable for making thin TMDC samples. Following this demonstration, we applied similar methodologies, however here to the more strongly bonded 3*d* ion intercalated TMDCs.


Following standard techniques used in specimen sectioning [14], we embedded  $Mn_{0.25}TaS_2$  and  $Fe_{0.25}TaS_2$  bulk crystals with lateral dimensions of  $\sim 500 \,\mu\text{m}$  in transparent epoxy (Epofix cold-setting embedding resin) for cutting in a Leica EM UC6 ultramicrotome. After mixing resin and hardener, the epoxy was heated for a few minutes in an oven at 60 °C in order to lower its viscosity and remove air bubbles. Afterwards, we covered the bottom of  $15 \,\text{mm} \times 7 \,\text{mm-sized}$  molds with a thin epoxy film and cured the epoxy for  $\sim 30$  min at 60 °C. Then we cut scratches in the epoxy layers using a razor blade, introduced bulk crystals in an upright position and filled the rest of the molds with epoxy. After another  $\sim$  3 h of curing at 60 °C, the epoxy blocks were ready for sectioning. Epoxy blocks were trimmed to expose the *ab*-plane of the sample material. After pre-sectioning with a glass knife, a diamond knife (dEYEmond ULTRA 45°) was used to produce thin sections from the block face. These were transferred onto square mesh copper TEM grids using a metallic loop suspending the sections in a thin water film ('perfect loop'). As read out from the ultramicrotome settings, we were able to obtain large area sections from 250 nm down to 30 nm in thickness. We found that Mn<sub>0.25</sub>TaS<sub>2</sub> was more easily sectioned than Fe<sub>0.25</sub>TaS<sub>2</sub>, which had a tendency to disintegrate during cutting. We attribute this to deformations of the Fe<sub>0.25</sub>TaS<sub>2</sub> lattice induced during the clipping of a small fraction from a spatially more extended crystal platelet. For Mn<sub>0.25</sub>TaS<sub>2</sub> in contrast, we had suitably sized bulk crystals available from the start.

While sample thicknesses were as-read from the microtome settings, the  $Mn_{0.25}TaS_2$  sample displayed in figure 1(c) was also tested via electron energy loss spectroscopy (EELS) to assess the thickness [27]. Assuming an effective atomic number of Z = 34, thickness measurements of three locations of the sample resulted in values ranging from 80 nm to 100 nm (with  $\pm 20\%$  accuracy), in close agreement with the 100 nm as-read value. Furthermore, all measurements relating to structural (electron diffraction) and magnetic (x-ray dichroism) properties remain qualitatively similar regardless of thickness.

#### 4. Characterization

#### 4.1. Optical microscopy

Optical microscopy was conducted for every sample, representative images of which are shown in figures 1(c) and (d). The sectioned samples showed large lateral areas of several hundreds of microns for  $Mn_{0.25}TaS_2$  and slightly smaller for  $Fe_{0.25}TaS_2$ , and a good adhesion to the grids.




**Figure 2.** Selected area electron diffraction (SAED) images of (a) 50 nm sample of  $Mn_{0.25}TaS_2$ , and (b) 200 nm sample of  $Fe_{0.25}TaS_2$ . Weak superlattice spots are visible in both diffraction patterns halfway between the structural reflections of 2*H*-TaS<sub>2</sub>. The images are scaled to accommodate different camera lengths.

In the optical images, we can identify regions of the samples that appear grooved. This is most easily seen as horizontal lines near the bottom of figure 1(c). The grooves correspond to the cutting direction of the ultramicrotome and indicate imperfections that develop during multiple uses of the diamond knife. In [26], it is suggested that this is caused by a reaction of the tantalum with the diamond blade. In our studies, we did not use a virgin knife, and thus we are unable to classify the origin of the knife damage. However, over the course of many cuts, we note that the density of scratches and nicks in the blade did not noticeably increase, while the sample quality remained unchanged.

Despite the structural inhomogeneities that are caused by our preparation technique, we presently do not witness modifications to the sample magnetic properties, for example due to cut-induced strain. In particular, in the x-ray studies presented below, the onset of magnetic properties occurs at the same temperature (within 10 K) of the pre-cut bulk samples (measured using MPMS). We take this as an indication of limited strain-induced modification to the magnetic properties.

#### 4.2. Transmission electron diffraction

In order to verify the crystallinity of the sectioned samples, and particularly to investigate the ordering of intercalated ions, we recorded selected area electron diffraction (SAED) patterns in a TEM. Images recorded at 200 keV electron energy are shown in figure 2. For Fe<sub>0.25</sub>TaS<sub>2</sub>, a thinner edge region was required in order to clearly witness a nice diffraction pattern. Importantly, both diffraction patterns exhibit the expected superlattice reflections midway between the structural reflections of the host lattice, indicative of the  $2 \times 2$  ordering of the intercalants. Furthermore, we observe no sign of a  $\sqrt{3} \times \sqrt{3}$  superlattice which would emerge in case of intercalant excess or disorder [28]. In general, good quality diffraction patterns were acquired on the thinnest samples (XMCD measurements discussed below can be performed on all sample thicknesses), while Mn<sub>0.25</sub>TaS<sub>2</sub> showed better spatial homogeneity in intercalant concentration than Fe<sub>0.25</sub>TaS<sub>2</sub>.




**Figure 3.** X-ray absorption spectra  $\mu_{\pm}$  (red) for (a) 150 nm sample of Mn<sub>0.25</sub>TaS<sub>2</sub>, and (b) 200 nm sample of Fe<sub>0.25</sub>TaS<sub>2</sub>, for two orientations of applied magnetic field. The sample and applied field were rotated 40° with respect to the incoming beam for Mn<sub>0.25</sub>TaS<sub>2</sub>, while Fe<sub>0.25</sub>TaS<sub>2</sub> was acquired at normal incidence. XMCD spectra are shown in blue. The asymmetry in  $L_3$  and  $L_2$  for the case of Fe<sub>0.25</sub>TaS<sub>2</sub> indicates a large unquenched orbital moment.

#### 4.3. XMCD spectroscopy

To assess the magnetic properties of the thinned samples, x-ray magnetic circular dichroism (XMCD) measurements in a transmission geometry were performed using the ALICE chamber at beamline PM3 of the BESSY II synchrotron at Helmholtz-Zentrum Berlin. The ALICE chamber features a liquid helium cooled sample holder and an electromagnet, both of which rotate with respect to the incoming beam direction and facilitate the study of both out-of-plane and in-plane magnetization characteristics. Details on the broader versatility of ALICE can be found in [29]. Measurements were conducted at a range of temperatures below the respective Curie temperatures of the two samples. Full spectroscopic information over the  $L_{3,2}$  absorption edges of Fe and Mn was collected. Since XMCD is sensitive to the magnetization component parallel to the x-ray wave vector, measurements of  $Fe_{0.25}TaS_2$ were performed at normal incidence, while  $Mn_{0.25}TaS_2$  (and the applied field) was rotated by an angle  $\Theta$  with respect to the x-ray beam direction to maximize the projection of the magnetization onto the x-ray wave vector. Rotation angles achieved did not exceed 40° from normal. For a fixed x-ray helicity, the direction of the magnetic field was switched, and the transmitted intensity was acquired for oppositely magnetized films, denoted as  $I_+$  and  $I_-$ , from which we calculate the absorption cross sections  $\mu_{\pm} = -\log(I_{\pm}/I_0)$  for the two magnetization directions ( $I_0$  is the incident photon flux).

Figure 3 shows representative x-ray absorption spectra  $\mu_{\pm}$  (red) for Mn<sub>0.25</sub>TaS<sub>2</sub> and Fe<sub>0.25</sub>TaS<sub>2</sub> across the respective  $L_{3,2}$  edges for both orientations of the magnetic field. Included in the figure is the extracted XMCD signal  $\mu_{XMCD}$  (blue) for the two materials, calculated following standard treatments for XMCD analysis [30, 31]:



**Figure 4.** Hysteresis curves at the  $L_3$  edge of (a) 50 nm sample of Mn<sub>0.25</sub>TaS<sub>2</sub>, and (b) 200 nm sample of Fe<sub>0.25</sub>TaS<sub>2</sub>. Note the different field strengths for the two samples.

$$\mu_{\rm XMCD}(E) = \frac{1}{\gamma \cos(\Theta)} [\mu_{+}(E) - \mu_{-}(E)].$$
(1)

The XMCD signal has been corrected for both angle of incidence  $\Theta$  and degree of helicity of the source  $\gamma$ . We used  $\gamma \approx 0.925$  which is characteristic for the off-axis emission of the bend magnet radiation at beamline PM3 (specifically at the Fe *L* edge) [32].

A cursory comparison between the XMCD spectra for the two materials unveils a notable difference, namely, the integrated intensity of the  $L_{3,2}$  edges are vastly different. As is well known from XMCD analysis, differences in the integrated intensity at the two edges is a manifestation of varying degrees of spin and orbital contributions to the total magnetization.

Applying sum rules to the respective edges, we can extract the ratio of orbital to spin magnetic moment [31]:

$$\frac{m_{\rm orb}}{m_{\rm spin}} = \frac{2q}{9p - 6q} \tag{2}$$

where p represents the area under the  $L_3$  edge, and q the overall area under both absorption edges:

$$p = \int_{L_3} \mu_{\text{XMCD}}(E) \,\mathrm{d}E \tag{3}$$

$$q = \int_{L_3+L_2} \mu_{\text{XMCD}}(E) \, \mathrm{d}E. \tag{4}$$

The measured ratio of orbital to spin magnetic moment for  $Fe_{0.25}TaS_2$  is found to be 0.39(4) and in close agreement with previously obtained values of 0.33 [19]. Meanwhile the measured value for  $Mn_{0.25}TaS_2$  is -0.06(6), which to our knowledge is the first direct measurement of the fully quenched orbital moment in this material. Previously, the existence of a quenched orbital moment was inferred by the isotropic magnetic susceptibility in the paramagnetic phase [8]. The results and corresponding error bars are derived from the ensemble of measurements below 50 K and 110 K for  $Mn_{0.25}TaS_2$  and  $Fe_{0.25}TaS_2$ , respectively.

As a final measurement, hysteresis curves were obtained at the peak of the  $L_3$  edge for both samples, as shown in figure 4. In the case of  $Mn_{0.25}TaS_2$ , the hysteresis vanishes above 90 K, in close agreement with our independent measurements on the bulk samples prior to sectioning ( $T_{\rm C} = 96$  K) using a magnetic property measurement system (MPMS). This lies 10 K above the literature value of 80 K [8] mentioned at the outset and indicates good sample quality, since off-stoichiometry drastically reduces the ferromagnetic transition temperature in 3dion intercalated TMDCs [33]. For  $Fe_{0.25}TaS_2$ , we measure a Curie temperature of  $\sim 110$  K, which agrees reasonably well with our independent MPMS measurements on the bulk samples (in zero-field-cooled measurements, we witness a broad transition region extending from 160 K to 120 K). However, the measured transition temperature lies below the literature value of 155 K [18] for phase pure  $Fe_{0.25}TaS_2$ , and is likely indicative of regions of off-stoichiometry [33]. This is also corroborated by our SAED results which indicate a degree of spatial inhomogeneity. Nonetheless, the expected high coercivity of the iron intercalated sample as compared to the manganese intercalated sample is clearly visible.

#### 5. Conclusion and outlook

In conclusion, we prepared free-standing thin films of magnetic ion intercalated transition metal dichalcogenides using ultramicrotoming techniques. Thicknesses ranging between 30 nm and 250 nm were achieved and characterized by transmission electron diffraction and XMCD spectroscopy. Using transmission electron diffraction, we witness the intercalant  $2 \times 2$  crystallographic ordering in both materials, a characteristic of the intercalation concentration y = 1/4. Using XMCD spectroscopy, we measured the orbital contribution to the total magnetization for the two materials. Thin films facilitate true absorption measurements, and are preferred for quantitative measurements over fluorescence and electron yield geometries. This has allowed us to verify the unquenched orbital moment in Fe<sub>0.25</sub>TaS<sub>2</sub>, as well as the fully quenched orbital moment in Mn<sub>0.25</sub>TaS<sub>2</sub>.

Looking ahead, we note that thin films of intercalated dichalcogenides have wide applicability in time-resolved x-ray and electron diffraction studies. In both cases, the sample thickness can be optimized to easily match the absorption depth of both pump and probe pulses, ensuring that measurements are performed on uniformly excited materials. With respect to time-resolved XMCD [34, 35], we foresee the capability of measuring magnetization dynamics of 'local moment' orbital and spin components on the intercalant site, as well as dynamics of itinerant conduction electrons of the host lattice (measured at a suitable host absorption edge). Due to the RKKY interaction, conduction electrons acquire a modest spin polarization which we expect exhibits different magnetization dynamics. In the broader context of intercalated dichalcogenides, as one measures dynamics in a variety of members of this family, the orbital, spin, and conduction electron contribution to the total magnetization can be varied, providing a robust platform on which to study ultrafast magnetism.

Finally, we also envisage a range of time-resolved coherent x-ray scattering measurements to resolve the dynamics of magnetic domains on sub-picosecond timescales, and length scales of a few tens of nanometers. For the case of ultrafast transmission electron microscopy (UTEM) [36, 37], thin magnetic films open the door to ultrafast Lorentz microscopy, thus providing a measure of magnetic domain motion and domain wall dynamics on timescales approaching femtoseconds, and spatial length scales of a few nanometers [38].

#### Acknowledgments

The authors thank P Pourhossein Aghbolagh and R Chiechi for discussions and instructions on the use of the ultramicrotome, as well as N Rubiano da Silva, M Möller, and J Momand for help with TEM diffraction images, A Feist for assistance with EELS spectroscopy, and the HZB for the allocation of synchrotron radiation beamtime at BESSY II. Synchrotron work was supported by F Radu and T Kachel. TD, CR, and RT thank the German Academic Exchange Service (DAAD) for support within the framework of the U4 University Network during TD's stay in Groningen. XZ acknowledges support from the National Natural Science Foundation of China (Grant No. 11204312) for work conducted at the High Magnetic Field Lab (Hefei). The work at Rutgers University was supported by the NSF under Grant No. NSF-DMREF-1233349, and the work at Postech was supported by the Max Planck POSTECH/KOREA Research Initiative Program (Grant No. 2011-0031558) through NRF of Korea funded by MSIP. The research leading to these results has received funding from the European Community's Seventh Framework Programme (FP7/2007–2013) under Grant Agreement No. 312284.

#### References

- [1] Wilson J and Yoffe A 1969 Adv. Phys. 18 193
- [2] Wang Q H, Kalantar-Zadeh K, Kis A, Coleman J N and Strano M S 2012 Nat. Nanotechnol. 7 699
- [3] Dean N, Petersen J C, Fausti D, Tobey R I, Kaiser S, Gasparov L V, Berger H and Cavalleri A 2011 Phys. Rev. Lett. 106 016401
- [4] Hellmann S et al 2012 Nat. Commun. 3 1069
- [5] Huang X, Zeng Z and Zhang H 2013 Chem. Soc. Rev. 42 1934
- [6] Jariwala D, Sangwan V K, Lauhon L J, Marks T J and Hersam M C 2014 ACS Nano 8 1102
- [7] Zhu Z Y, Cheng Y C and Schwingenschlögl U 2011 Phys. Rev. B 84 153402
- [8] Parkin S S P and Friend R H 1980 *Phil. Mag.* B **41** 65
- [9] Eichberger M, Schäfer H, Krumova M, Beyer M, Demsar J, Berger H, Moriena G, Sciaini G and Miller R J D 2010 *Nature* 468 799
- [10] Zhu P et al 2013 Appl. Phys. Lett. 103 071914
- [11] Sun S, Wei L, Li Z, Cao G, Liu Y, Lu W J, Sun Y P, Tian H, Yang H and Li J 2015 *Phys. Rev. B* 92 224303
- [12] Möhr-Vorobeva E, Johnson S L, Beaud P, Staub U, De Souza R, Milne C, Ingold G, Demsar J, Schaefer H and Titov A 2011 Phys. Rev. Lett. 107 036403

- [13] Nakajima R, Stöhr J and Idzerda Y U 1999 *Phys. Rev.* B 59 6421
- [14] Malis T F and Steele D 1990 MRS Proc. 199 3
- [15] Revelli J F and Disalvo F J 1979 Inorg. Synth. 19 35
- [16] Vandenberg-Voorhoeve J M 1976 Optical and Electrical Properties (Physics and Chemistry of Materials with Layered Structures vol 4) ed P A Lee (Dordrecht: Reidel) pp 423–57
- [17] Hinode H, Ohtani T and Wakihara M 1995 J. Solid State Chem. 114 1
- [18] Vannette M D, Yeninas S, Morosan E, Cava R J and Prozorov R 2009 Phys. Rev. B 80 024421
- [19] Ko K-T, Kim K, Kim S B, Kim H-D, Kim J-Y, Min B I, Park J-H, Chang F-H, Lin H-J, Tanaka A and Cheong S-W 2011 Phys. Rev. Lett. 107 247201
- [20] Motizuki K, Suzuki N and Tomishima S 1992 J. Magn. Magn. Mater. 104–7 681
- [21] Ōnuki Y, Ina K, Hirai T and Komatsubara T 1986 J. Phys. Soc. Japan 55 347
- [22] Morosan E, Zandbergen H W, Li L, Lee M, Checkelsky J G, Heinrich M, Siegrist T, Ong N P and Cava R J 2007 *Phys. Rev.* B 75 104401
- [23] Zeng Z, Yin Z, Huang X, Li H, He Q, Lu G, Boey F and Zhang H 2011 Angew. Chem., Int. Ed. 50 11093
- [24] Coleman J N et al 2011 Science 331 568
- [25] Liang W Y 1986 Intercalation in Layered Materials (NATO ASI Series—Series B: Physics vol 148) ed M S Dresselhaus (New York: Springer) pp 31–73

- [26] Eichberger M, Krumova M, Berger H and Demsar J 2013 Ultramicroscopy 127 9
- [27] Malis T, Cheng S and Egerton R 1988 J. Electron Microsc. Tech. 8 193
- [28] Choi Y J, Kim S B, Asada T, Park S, Wu W, Horibe Y and Cheong S-W 2009 Europhys. Lett. 86 37012
- [29] Abrudan R, Brüssing F, Salikhov R, Meermann J, Radu I, Ryll H, Radu F and Zabel H 2015 *Rev. Sci. Instrum.* 86 063902
- [30] O'Brien W L and Tonner B P 1994 Phys. Rev. B 50 12672
- [31] Chen C T, Idzerda Y U, Lin H-J, Smith N V, Meigs G, Chaban E, Ho G H, Pellegrin E and Sette F 1995 Phys. Rev. Lett. 75 152
- [32] Kachel T, Eggenstein F and Follath R 2015 J. Synchrotron Radiat. 22 1301
- [33] Hardy W J, Chen C-W, Marcinkova A, Ji H, Sinova J, Natelson D and Morosan E 2015 Phys. Rev. B 91 054426
- [34] Radu I et al 2011 Nature 472 205
- [35] Bergeard N, Lopez-Flores V, Halté V, Hehn M, Stamm C, Pontius N, Beaurepaire E and Boeglin C 2014 Nat. Commun. 5 3466
- [36] Lobastov V A, Srinivasan R and Zewail A H 2005 Proc. Natl Acad. Sci. 102 7069
- [37] Feist A, Echternkamp K E, Schauss J, Yalunin S V, Schäfer S and Ropers C 2015 Nature 521 200
- [38] Park H S, Baskin J S and Zewail A H 2010 Nano Lett. 10 3796